




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>G02B 27/22, H04N 13/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/08145</b> <b>(43) International Publication Date:</b> 18 February 1999 (18.02.99)
<b>(21) International Application Number:</b> PCT/GB98/02360 <b>(22) International Filing Date:</b> 6 August 1998 (06.08.98)  <b>(30) Priority Data:</b> 9716689.6      7 August 1997 (07.08.97)      GB  <b>(71) Applicant (for all designated States except US):</b> ISIS INNOVATION LIMITED [GB/GB]; 2 South Parks Road, Oxford OX1 3UB (GB).  <b>(72) Inventors; and</b> <b>(75) Inventors/Applicants (for US only):</b> PAIGE, Edward, George, Sydney [GB/GB]; 6 Mill Lane, Horton-Cum-Studley, Oxfordshire OX33 1DH (GB). NEIL, Mark, Andrew, Aquilla [GB/GB]; 22 Poplar Road, Botley, Oxford, Oxfordshire OX2 9LB (GB). SUCHAROV, Leon, Oliver, Dylan [GB/GB]; 60 Bernwood Road, Barton, Oxford, Oxfordshire OX3 9LQ (GB).  <b>(74) Agent:</b> PERKINS, Sarah; Stevens, Hewlett & Perkins, 1 Serjeants' Inn, Fleet Street, London EC4Y 1LL (GB).		<b>(81) Designated States:</b> CA, JP, KR, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** THREE DIMENSIONAL IMAGE DISPLAY**(57) Abstract**

The 3-D image display consists of a pixellated display (11) that is illuminated through a beam splitter (16). A plan mirror (17) is provided on a movable mount (15) so that the mirror may be moved towards or away from an objective lens (12) positioned between the mirror (17) and the beam splitter (16). A quarter wave plate (18) is provided between the beam splitter (16) and the mirror (17) so that light reflected back from the mirror (17) through the quarter wave plate (18) passes straight through the beam splitter (16) to an eyepiece lens (13). Movement of the mirror (17) enables the mirror (17) to act as an optical path length modifier and permits an image from the display (11) to be presented at different focal positions. Rapid cycling through different focal positions results in the image being perceived as a 3-D image. As the objective lens (12) is positioned between the beam splitter (16) and the mirror (17), the objective lens (12) also acts as a demagnifying lens for images from the display (11). Preliminary demagnification of the image reduces the distances the mirror (17) is required to travel to provide the desired changes in focal position. This in turn reduces the demands on the performance of the mount (15), that are considerable in conventional systems where no demagnification is performed. In this way simple optical and mechanical components may be employed in the image display to generate perceived three dimensional images.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

### THREE DIMENSIONAL IMAGE DISPLAY

The present invention relates to a three dimensional (3-D) image display of the type in which a series of two dimensional (2-D) images in  
5 different depth planes are presented in succession sufficiently rapidly that the series of images is perceived as a 3-D image. In particular, but not exclusively, the 3-D image display is suited for use in a stereo head mounted display system.

In general, for a head mounted display a pair of microdisplay  
10 devices, such as a ferroelectric liquid crystal spatial light modulators (FLCSLM), are employed to display two images which are separately viewed through a series of lenses by each of the viewer's eyes so that the image is viewed at infinity or some other fixed distance. Figure 1 shows a conventional microdisplay projection system for one eye consisting of the  
15 FLCSLM 1, an objective lens 2 and an eyepiece lens 3. In practice a parallel lens system for the other eye would also be provided. The lenses provide the magnification necessary for the image displayed by the FLCSLM to be seen. In Figure 1,  $d$  denotes the size of an individual pixel of the FLCSLM which subtends an angle  $\theta$  as seen by the viewer. Of  
20 course the image display system shown in Figure 1 is for the display of a two dimensional image. To enable this system to display 3-D images it has previously been suggested that one of the fixed lenses, preferably the objective lens, be replaced by a variable focus lens or in a folded system by a deformable mirror so that the image generated by the first FLCSLM  
25 may be presented to the viewer's eye sequentially at different focal positions and perceived as a 3-D image.

The present invention proposes an alternative display system which enables 3-D images to be perceived by a viewer which avoids the significant expense and other undesirable features of a variable focus lens  
30 or deformable mirror.

The present invention provides a 3-D image display comprising a display, a demagnifying lens for demagnifying an image generated by the display; a lens system for focussing the demagnified image and a controllable optical path length modifier for adjusting the optical path length through the image display whereby an image generated by the display can be focussed to sequentially appear at a plurality of different focal positions.

The optical path length modifier may be in the form of a drive unit for axially moving one or more optical components of the image display. Alternatively, the optical path length modifier may be in the form of a variable refractive index plate or an electro-optic modulator.

With the present invention, as the image generated by the display is initially demagnified, the variation in optical path length necessary to focus the image at appropriate focal positions is significantly reduced. In this way simple optical and mechanical components may be employed in the image display to generate perceived three dimensional images. Moreover, the 3-D image display is particularly suited to a head mounted display.

Embodiments of the present invention will now be describe by way of example only with reference to the accompanying drawings, in which:

Figure 1 is a diagram of a conventional image display system;  
Figure 2 is a diagram of a first embodiment of a 3-D image display in accordance with the present invention; and

Figure 3 is a diagram of a second embodiment of a 3-D image display in accordance with the present invention.

In Figure 2 a modified version of the conventional image display system of Figure 1 is shown consisting of a FLCSLM 11, an objective lens 12 and an eyepiece lens 13 along with a demagnifying lens 14 located between the FLCSLM 11 and the objective lens 12. The demagnifying lens 14 generates a scaled down image in plane P' of the image generated by the FLCSLM 11. This demagnification is accommodated by the remainder of the lens system, lenses 12 and 13, which provides a greater

magnification than for the display system of Figure 1 so that the size of the image seen by the viewer is the same as for a conventional image display system.

In addition, it will be seen from Figure 2 that the objective lens 12 is  
 5 housed in a piezoelectrically movable mount 15 which enables the objective lens 12 to be moved axially towards and away from the image plane P<sup>1</sup>. The movable mount 15 or other suitable means provides a controlled movement of the objective lens along the axis of the display system.

10 With the image display shown in Figure 2, movement of the objective lens 12 towards or away from the image plane P<sup>1</sup> changes the apparent focal position of the image perceived by the viewer. For example, to achieved an apparent focal position of the image at a distance V from the viewer, the objective lens must be moved a distance Δ from the  
 15 position of the objective lens where the image is projected at infinity, in accordance with the following approximate relationship:

$$\Delta = (M^2/V) \cdot (d^2/\theta^2)$$

Where M is the magnification of the demagnifying lens 14. A similar effect can be achieved by mounting the eyepiece lens on the movable mount 15  
 20 and moving the eyepiece lens the same distance Δ or by moving both the FLCSLM and the demagnifying lens.

In this way, movement of the objective (or eyepiece) lens to different positions successively will present the 2-D images at different perceived distances and if this is done sufficiently quickly the viewer perceives the  
 25 image as three dimensional. However, the objective lens 12 must be moved very quickly if the image perceived by the viewer is to be 3-D. To achieve a flicker free 3-D image a complete sequence of images at different perceived distances must be produced ideally faster than video rates, for example in less than 40ms. By demagnifying the image  
 30 generated by the FLCSLM, the actual distance which the objective lens 12

must travel is scaled by a factor  $M^2$  thereby making the generation of 3-D images in this manner feasible.

For example, without initial demagnification of the image produced by a conventional FLCSLM having  $15\text{ }\mu\text{m}$  pixels ( $d=15\text{ }\mu\text{m}$ ), to generate  
5 the image at a perceived distance of  $V=1\text{ m}$  with an angular extent of 30 degrees with  $256 \times 256$  pixels, then  $\theta=30^\circ/256$  and the objective lens would need to be moved by  $\Delta=54\text{ }\mu\text{m}$ . To achieve a perceived distance of  $V=15\text{ cm}$ , an axial shift of the lens of  $\Delta=360\text{ }\mu\text{m}$  would be needed. Although these axial distances are small, the lens must be move through  
10 these distances in a very short time. As an example, taking the greater distance of  $\Delta=360\text{ }\mu\text{m}$  and allowing for only four separate perceived distances within the 40 ms time frame and with each image position held still for a period of time of 5 ms; the movement step would require a cycle of acceleration/deceleration of up to  $57.6\text{ m/s}^2$ . This type of  
15 acceleration/deceleration and the resolution of the axial travel necessary for an operational imaging system, would be difficult to achieve with a mechanism which is sufficiently light and compact that it can form part of a head mounted display. By including initial demagnification of, for example,  $M=1/3$ , the axial shift for a perceived distance of 15 cm is reduced to  $40\text{ }\mu\text{m}$   
20 which in turn significantly reduces the necessary acceleration/deceleration requirements.

In Figure 3 a folded image display system is shown in which the microdisplay 11 is used in a reflective mode with a polarising beam splitter 16 provided between a polarised light source (not shown) and the FLCSLM  
25 11. With this image display system the objective lens 12 also functions as the demagnifying lens with the image passing through the lens 12 to a mirror 17, which is mounted on the movable mount 15, and back through the lens.

In use, linearly polarised light passes through the beam splitter 16  
30 and is reflected back by the FLCSLM 11. The reflected light from the

FLCSLM, which contains an image in light with polarisation rotated through 90°, is reflected by the beam splitter 16 through a quarter wave plate 18 towards the objective lens 12. The objective lens 12 demagnifies the image from the beam splitter 16 to produce a demagnified image in the image plane P<sup>1</sup>. The mirror 17 placed at or near P<sup>1</sup> reflects the demagnified image back towards the objective lens 12 which refocuses the image to plane P<sup>2</sup>. The double pass through the quarter wave plate 18 ensures that the polarisation of the image is rotated through 90° thereby ensuring the image passes straight through the beam splitter 16 to the eyepiece lens 13. With the mirror 17 at image plane P<sup>1</sup>, the viewer perceives the image at infinity. Movement of the mirror 17 away from the image plane P<sup>1</sup> results in the image being perceived at a finite distance. Unlike the image display of Figure 2, as this is a folded optical system the mirror 17 need only be moved a distance  $\Delta/2$  to achieve any desired perceived distance.

In an adaption of the optical arrangement shown in Figure 3, the polarising beam splitter 16 may be positioned adjacent the FLCSLM 11, off the main optical path through the apparatus, and the quarter wave plate 18 may be replaced with a non-polarising beam splitter, for example a pellicle beam splitter. With this adaption chromatic aberration can be reduced and the flexibility in the arrangement of the binocular display can be increased because the channels to each eye may be differentiated by polarisation, if it is so wished. The main disadvantage with this arrangement, however, is that around 75% of light is lost.

Furthermore, a pixellated shutter 19 such as an SLM may be included in the 3-D optical system. The SLM shutter 19 is indicated by broken lines in Figure 3. Particularly when the 3-D image display is used in a head mounted form, each pixel of display 11 contributes to one image plane and one plane only, because of the small angle of view. Hence, the display 11 can exhibit all the image planes at the same time. The SLM

shutter 19 is then used to transmit only the images from pixels of the display 11 appropriate for a particular plane. By synchronising the shutter action of the SLM shutter 19 with the movement of the mount 15, each image plane is transmitted cyclically by the shutter 19 to the eyepiece.

- 5 This means that the display can be relatively slow (say 50 Hz, i.e. video rate) and rich in information (many colours, many grey levels) whilst the SLM shutter 19 operates at the much fast rate of the mount 15. Preferably, the SLM shutter 19 is positioned adjacent the display 11. However, there may be occasions where it is necessary to position the shutter away from  
10 the display, but still in an image plane of the display, in which case, the shutter must accommodate any changes in magnification of the image.

With both of the display systems described above refocusing of the image perceived by the viewer is achieved by the mechanical axial shift of one or more of the optical components of the system, e.g. the objective  
15 lens (Figure 2) and the mirror (Figure 3). However, in each case the refocusing is achieved because the optical path within the display system has been lengthened or reduced by a distance  $\Delta$  in that part of the display system where a demagnified real or virtual image is projected. Of course there are alternative ways in which the optical path can be altered without  
20 movement of the individual optical components of the system. For example, a variable refractive index plate may be introduced into the display system in the vicinity of P<sup>1</sup>. The variable refractive index device may be, for example, in the form of an electro-optic modulator or may be a plate such as a glass disc with sectors of varying thickness which can be  
25 rotated to intersect the optical path through the display system in sequence thereby achieving the necessary sequential path length variations.

It will be apparent that the output aperture of the display system is limited in size which has the effect of restricting the position of the viewer's eye. However, this is not a problem where the image display is to be used  
30 as a head mounted 3-D display as the viewer's position relative to the

display is of necessity fixed. There is a secondary effect associated with the restriction on the size of the output aperture; as the exit pupil of the display system becomes smaller than the pupil of the viewer's eye, the apparent depth of focus will appear larger for all objects. With optical

5 systems of the type described above based on a 'microscope' design, the size of the output aperture is limited by the aperture of the objective lens and the magnification and position of the eyepiece lens. Particular display system architectures may therefore be selected to optimise the output aperture as far as the viewer is concerned. Moreover, appropriate

10 selection of the system architecture is also necessary to ensure that the angular field of view seen by the viewer is constant for all perceived distances.

It will, of course, be appreciated that limited or defective focusing of an individual's eyes can be corrected for, once the characteristics of the

15 problem are known.

As the changes in the image depth are achieved by the linear movement or rotation of a single component, the resulting aberrations introduced as the image is refocused are low compared to conventional 3-D display systems. Also, in a linear system by ensuring initial

20 demagnification of the image which reduces the distance it is necessary to move the optical element, the power consumption is reduced and the associated noise and vibration can be minimised. The display system has the further advantage that it has the potential to transmit 100% of the input light which is a great improvement over conventional systems which

25 employ either a FLCSLM variable focus lens or deformable mirror both of which are inefficient. Moreover, with a FLCSLM acting as a variable lens, that part of the light which is not refocused can lead to degradation in image contrast. Conventional systems which employ a FLCSLM as a variable lens have a further disadvantage in that such systems suffer from

30 achromatic aberrations which is not a problem of the display systems

describe above.

Although the 3-D image displays have been described with reference to a head mounted display, of course the image displays are suitable for use in other applications such as in ophthalmology equipment or  
5 indeed in any circumstances where rapid refocusing of images is required.

## CLAIMS

1. A 3-D image display comprising a display, a demagnifying lens for demagnifying an image generated by the display, a lens system for focussing the demagnified image and a controllable optical path length modifier for adjusting the optical path length through the image display whereby an image generated by the display can be focussed to sequentially appear at a plurality of different focal positions.
2. A 3-D image display as claimed in claim 1, wherein the optical path length modifier is in the form of a variable refractive index plate or an electro-optic modulator.
3. A 3-D image display as claimed in claim 1, wherein the optical path length modifier is in the form of a drive unit for axially moving one or more optical components of the image display.
4. A 3-D image display as claimed in claim 3, wherein the drive unit is piezoelectrically operable.
5. A 3-D image display as claimed in either of claims 3 or 4, wherein the drive unit includes a mount in which one or more elements of the focusing lens system is mounted.
6. A 3-D image display system as claimed in any one of the preceding claims, wherein the image display system is folded and includes a polarising beam splitter, a mirror and a retardation plate positioned between the beam splitter and the mirror.

7. A 3-D image display system as claimed in claims 5 and 6, wherein the mirror is mounted on the drive unit.
8. A 3-D image display system as claimed in any one of claims 6 or 7,  
5 wherein the demagnifying lens is also the objective lens of the focusing lens system.
9. A 3-D image display as claimed in any one of the preceding claims, wherein the display is a spatial light modulator.
- 10
10. A 3-D image display as claimed in claim 9, wherein a pixellated shutter is provided for transmitting images from pixels of only one image plane.
- 15 11. A 3-D image display as claimed in claim 10, wherein the pixellated shutter is a spatial light modulator.
12. A head mounted display including the 3-D image display as claimed in any one of the preceding claims.
- 20

1/2




FIGURE 1




FIGURE 3




FIGURE 2

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 98/02360

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 G02B27/22 H04N13/00

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 G02B H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 84 04193 A (BRUKER MEDIZINTECH) 25 October 1984 see page 10 - page 16; figures 1,2 ---	1,3,5,7, 8
A	EP 0 785 457 A (NIPPON TELEGRAPH & TELEPHONE) 23 July 1997 see column 36 - column 37; figures 40,42 ---	2
A	EP 0 385 705 A (TEXAS INSTRUMENTS INC) 5 September 1990 see column 8; figure 1 ---	1,9-11
A	WO 93 21673 A (BANDGAP TECH CORP) 28 October 1993 see column 7, line 30 - column 8, line 31; figure 2 -----	12

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

**Special categories of cited documents:**

"A" document defining the general state of the art which is not considered to be of particular relevance  
"E" earlier document but published on or after the international filing date  
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  
"O" document referring to an oral disclosure, use, exhibition or other means  
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention  
"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone  
"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.  
"&" document member of the same patent family

Date of the actual completion of the international search

10 November 1998

Date of mailing of the international search report

17/11/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

von Moers, F

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/02360

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 8404193 A	25-10-1984	DE 3313217 A	18-10-1984
		AU 2828684 A	07-11-1984
		DE 3473522 A	22-09-1988
		EP 0154624 A	18-09-1985
		JP 5002328 B	12-01-1993
		JP 60501045 T	11-07-1985
		US 4674837 A	23-06-1987
EP 0785457 A	23-07-1997	JP 9243960 A	19-09-1997
		JP 9297282 A	18-11-1997
		JP 9258271 A	03-10-1997
		JP 10048597 A	20-02-1998
		JP 10074052 A	17-03-1998
EP 0385705 A	05-09-1990	US 5128660 A	07-07-1992
		DE 69031477 D	30-10-1997
		DE 69031477 T	05-02-1998
		JP 3282492 A	12-12-1991
		US 5214419 A	25-05-1993
		US 5515076 A	07-05-1996
		US 5446479 A	29-08-1995
		US 5170156 A	08-12-1992
		US 5162787 A	10-11-1992
WO 9321673 A	28-10-1993	US 5325386 A	28-06-1994
		AU 4291593 A	18-11-1993
		CA 2133977 A	28-10-1993
		CN 1082228 A	16-02-1994
		EP 0637409 A	08-02-1995
		JP 7506220 T	06-07-1995